

# Fuel Mobile Dispenser Mini Gas Station Customization For Enterprise Use

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 set

China

Virette

15 work days

50 set per month

C1

- Price:
- Delivery Time:
- Payment Terms:
- Supply Ability:
- GB/T 3836.1-2021 1500USD-8000USD T/T, Western Union



### **Product Specification**

- Product:
- Barrier Material:
- Tank Volume:
- Rated Power:
- . Flow Range:
- Rated Voltage:
- Measuring Accuracy:
- Application:
- OEM:
- Highlight:
- Mobile Gas Station Honeycomb Aluminum 1-8 CBM 550-600W 40/65L/MIN 12V/24V/220V 99.7% Gasoline, Diesel, New Energy

220v mini gas station

Yes mini gas station customization, customization portable mini gas filling station,



#### **Product Description**

Product	Mobile fuel station
Tank Volume	1-8CBM
Barrier material	Honeycomb aluminum
Rated power	550-600W
Flow range	40/65L/MIN
Rated voltage	12V/24V/220V
Measuring accuracy	99.7%
Application	Gasoline, diesel, new energy

SIDAER provides you with safe, environmentally friendly, and multifunctional fuel oilstorage retail solutions. According to your on-site situation, you can choose betweenvertical or horizontal equipment, The input power can be AC220V, DC24V, or DC12V.

Our company provides DC12V photovoltaic panel power supply solutions, providing you with acomprehensive solution for fuel oil storage and retail.

The Gas Station adopts a safety and environmental protection design, which meetssafety and explosion-proof standards and has passed departmental acceptance.

The fuetank is designed with steel plate welding, which is pressure resistant, corrosion resistant, and leak free. The interior of the fuel tank is filled with barrier and explosion-proof materialsto eliminate the risk of detonation.

Ideal Use And Application

- \* Suburb, No gas station area
- \* Fleet, Construction site
- \* Farm, Agricultural machinery
- \* Town,Remote districts



### ● Standard △ Optional

Model	1000L 2 Nozzle	1500L 3 Nozzle	2000L 2 Nozzle	3000L 3 Nozzle	
Dimension L'W'H	1400*1050*1300	1400°1600°1300	2200° 1050° 1300	2200*1600*1300	
Weight	360KG	415KG	420KG	655KG	
Input Power	AC 220V DC 24V DC 12V				
Pump	Gear Pump ▲ Bennet Pump ▲ 12V/24V Mute Vane Pump ▲				
Flow Meter	FM 4B 65 Flow Meter				
Ex-proof Motor	AC 220VA DC 24VA DC 12VA				
Medium	Diesel Or Gasoline				
Flow	5L~60L/Min				
Vacuum	≥54KPa				
Accuracy	±0.3%				
Ex-proof Mark	Ex de lbmb IIB T4 GB				
Hose	3/4*				
Hose Length	4 M 🛑 6 M 🛆				
Nozzle	Automatic Nozzle 3/4*				
Break Away	3/4"				
Swivel	3/4*				
Option Device	Cuslom Appearance				
Option Device		IC Card	System		

Shizishu Industrial Concentration Zone, GuxiongStreet, Yuhuatai District, Nanjing City, Jiangsu Province, China