



4m Hose CNG Dispenser AC 220V 50Hz Gas Station Fuel Pump

Our Product Introduction

For more products please visit us on refueling-equipment.com

Basic Information

- Place of Origin: China
- Brand Name: Virette
- Delivery Time: 20 - 30 days



Product Specification

- Power Supply: AC 220V/50Hz
- Hose Length: 4m
- Nozzle: Single Or Dual
- Working Pressure: 20MPa
- Communication Interface: RS485/RS232
- Humidity Range: ≤95%
- Temperature Range: -25°C To +55°C
- Total Price Range: 0.01-999999.99
- Highlight: 50hz gas station fuel pump,
4m hose cng dispenser, cng dispenser ac 220v

Product Description

CD-100 CNG Gas Dispenser with Humidity Range $\leq 95\%$ and Temperature Range -25°C To 55°C

Product Description:

The Unit Price Range of the CNG Gas Dispenser is from 0.01-99.99, which gives you the flexibility to set different prices for different types of vehicles or fueling volumes. The Total Price Range of the CNG Gas Dispenser is from 0.01-999999.99, which means that you can cater to a wide range of customers with different fueling needs and budgets.

The CNG Gas Dispenser comes with an easy-to-read LCD Display that shows the fueling volume, unit price, and total price. The LCD Display is clear and bright, making it easy for your customers to read and understand their fueling costs. The CNG Gas Dispenser is easy to use, and it has a sturdy and durable construction that ensures long-lasting performance.

In conclusion, the CNG Gas Dispenser is an essential piece of CNG fueling equipment for any CNG filling station dispenser. It is accurate, reliable, and easy to use, with a wide range of pricing options and a clear LCD Display. If you're looking for a Natural Gas Fuel Pump that delivers high performance and durability, the CNG Gas Dispenser is the perfect choice for you.

Features:

Product Name: CNG Gas Dispenser

Communication Interface: RS485/RS232

Unit Price Range: 0.01-99.99

Display: LCD

Model: CD-100

Power Supply: AC 220V/50Hz

Other keywords: Natural Gas Fuel Pump, CNG Distribution Pump, CNG Refueling Machine

Technical Parameters:

Flow Rate	15-25L/min
Humidity Range	$\leq 95\%$
Total Price Range	0.01-999999.99
Power Supply	AC 220V/50Hz
Communication Interface	RS485/RS232
Working Pressure	20MPa
Display	LCD
Temperature Range	-25°C To $+55^{\circ}\text{C}$
Hose Length	4m
Accuracy	$\pm 0.5\%$

Applications:

The Virette CNG Gas Dispenser is suitable for a range of application occasions and scenarios. It can be used in CNG fill-up stations for natural gas vehicles, making it a great choice for fleet owners, public transportation companies, and private vehicle owners who want to reduce their carbon footprint and save money on fuel costs. The dispenser is also ideal for industrial and commercial settings, such as factories, warehouses, and large-scale construction sites, where CNG-powered equipment is used.

In addition, the Virette CNG Gas Dispenser is perfect for use in emergency situations, such as natural disasters or power outages. In these scenarios, the dispenser can be used along with a generator to provide a reliable source of energy for CNG-powered vehicles and equipment.

The Virette CNG Gas Dispenser is simple to operate and maintain, making it a cost-effective and efficient choice for CNG fueling equipment. With its high-quality components and advanced technology, the dispenser is designed to provide reliable and consistent performance, ensuring that your vehicles and equipment are always ready to go when you need them.

Customization:

Product Packaging:

1 CNG Gas Dispenser

1 User Manual

1 Power Cable

1 Filling Hose

1 Set of Keys

Shipping Information:

Shipping Method: Standard Ground Shipping

Estimated Delivery Time: 5-7 business days

Shipping Cost: Free

Shipping Restrictions: This product can only be shipped within the United States.

Packing and Shipping:



Virette Technology Co., Ltd.



+8615651807973



ryan.s@youngtioneotech.com



refueling-equipment.com

Shizishu Industrial Concentration Zone, GuxiongStreet, Yuhuatai District, Nanjing City, Jiangsu Province, China